


## FAST RECOVERY DIODE

## Outline drawings, mm



## Features

- Soft recovery, low noise
- High reliability

## Applications

- High speed power switching

## Maximum ratings and characteristics

- Absolute maximum ratings


Item	Symbol	Conditions	Rating	Unit
			-02	
Repetitive peak reverse voltage	$V_{RRM}$		200	V
Non-repetitive peak reverse voltage	$V_{RSM}$		200	V
Average output current	$I_o$	Square wave, duty=1/2, $T_c=100^\circ\text{C}$	20*	A
Surge current	$I_{FSM}$	Sine wave 10ms	80	A
Operating junction temperature	$T_j$		-40 to +150	$^\circ\text{C}$
Storage temperature	$T_{stg}$		-40 to +150	$^\circ\text{C}$

\*Average forward current of centertap full wave connection

- Electrical characteristics ( $T_a=25^\circ\text{C}$  Unless otherwise specified)


Item	Symbol	Conditions	Max.	Unit
Forward voltage drop	$V_{FM}$	$I_{FM}=5\text{A}$	1.25	V
Reverse current	$I_{RRM}$	$V_R=V_{RRM}$	500	$\mu\text{A}$
Reverse recovery time	$t_{rr}$	$I_F=0.1\text{A}, I_R=0.1\text{A}$	100	ns
		$I_F=0.1\text{A}, I_R=0.2\text{A}, I_{rec}=0.05\text{A}$	45	
Thermal resistance	$R_{th(j-c)}$	Junction to case	1.5	$^\circ\text{C/W}$

## Connection diagram




Characteristics


Forward characteristics




Reverse characteristics




Forward power dissipation




Output current-case temperature




Junction capacitance characteristics



Surge capability





廃型機種  
Discontinued product.